## **Declaration of Performance** No 04-DoP-2023/01



1.	Unique identification code of the product - type:	XPS-EN 13164-T2-CS(10\Y)300-TR200-DS(70,90)-DLT(2)5-WL(T)0	
2.	Identification of the construction product:	TEMAX XPS	
3.	Intended use/uses:	Thermal insulation for buildings	
4.	Manufacturer:	TEMAX BH d.o.o. Orašje, Bosnia and Herzegovina	
5.	Authorized representative:	Not relevant	
6.	System or systems of AVCP:	AVCP - System 3	
7.	Notified body/ies:	Notified testing laboratory No. 1404, No. 2477 and No. 2372	
8.	Harmonized standard:	EN 13164:2012+A1:2015	

Essential characteristics	Performance	Unit	Declared performance
Thermal resistance	Thickness	d <sub>N</sub> [mm]	50
	Thickness class	T	T2
	Thermal resistance	R <sub>D</sub> [m <sup>2</sup> K/W]	1,47
	Thermal conductivity	λ <sub>D</sub> [W/m K]	0,034
Reaction to fire	Reaction to fire	Euroclass	E
Release of dangerous substances	Release of dangerous substances		NPD
Acoustic absorption index	Sound absorption	AW	NPD
Continuous glowing combustion	Continuous glowing combustion		NPD
A/ B	Long-term water absorption by total immersion	WL(T) [vol.%]	0,7
Water Permeability	Long-term water absorption by diffusion	WD(V) [vol.%]	NPD
Compressive strength	Compressive stress or compressive strength	CS (10/Y)[kPa]	≥ 300
ensile/Flexural strength	Tensile strength perpendicular to faces	TR [kPa]	NPD
Durability of reaction to fire against heat, veathering, aging/degradation	Reaction to fire	Euro class	E
	Thermal resistance	R <sub>D</sub> [m <sup>2</sup> K/W]	1,47
Durability of thermal resistance against heat, weathering, aging/degradation	Thermal conductivity	λ <sub>D</sub> [W/m K]	0,034
	Freeze-thaw resistance after long-term water diffusion test	FTCD	NPD
	Freeze/thaw resistance after long-term water absorption by total immersion	FTCI	NPD
	Dimensional stability under specified temperature and humidity conditions	DS (70,90)	<5%
	Deformation under specified compressive load and temperature conditions	DLT	NPD
Durability of compressive strength against heat, weathering, aging/degradation	Compressive creep	CC (2/1,5/50)	NPD

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. This product does not contain Hexabromocyclodecane (declaration according to CPR requirement Article 6 Paragraph 5).

Signed for and on behalf of the manufacturer by:

Rustan Esati Production Director **TEMAX BH DOO** 

Orašje, Bosnia and Herzegovina 13.01.2023